

VERIFICATION OF COMPLIANCE

No.:	GZES2007022915PV
Applicant:	Shenzhen SOFAR SOLAR Co., Ltd. 401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community, XinAn Street, BaoAn District, Shenzhen City, Guangdong Province, P.R. China
Manufacturer:	Shenzhen SOFAR SOLAR Co., Ltd. 401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community, XinAn Street, BaoAn District, Shenzhen City, Guangdong Province, P.R. China
Product Name:	Hybrid Inverter (Three Phase)
Product Description:	Inverter used in PV system
Model No.:	HYD 5KTL-3PH, HYD 6KTL-3PH, HYD 8KTL-3PH; HYD 10KTL-3PH, HYD 15KTL-3PH, HYD 20KTL-3PH;
Trade Mark:	SSFAR

Rating:	Refer to page 2 to page 3
Intended Use:	PV System
Protection against Electric Shock:	Class I
Additional Information (if any):	IP 65
	Software Version: V2.00 Main DSP Software Version: D010136 Slave DSP Software Version: D010134

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard:	IEC 60068-2-1:2007 IEC 60068-2-14:2009	IEC 60068-2-2:2007 IEC 60068-2-30:2005
as shown in the		
Test Report Number(s):	GZES200702291501	

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards.



2020-08-25

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.



No.:

GZES2007022915PV

Other information added : Ratings

Model	HYD 5KTL-3PH	HYD 6KTL-3PH	HYD 8KTL-3PH	HYD 10KTL-3PH	HYD 15KTL-3PH	HYD 20KTL-3PH	
		PV Str	ing Input Data				
Max. DC voltage	1000V						
MPPT voltage range	180V~960V						
Full power MPPT voltage range	250V~850V	320V~850V	360V~850V	220V~850V	350V~850V	450V~850V	
Max. input current	12.5A/12.5A	12.5A/12.5A	12.5A/12.5A	25A/25A	25A/25A	25A/25A	
Max. short current	15A/15A	15A/15A	15A/15A	30A/30A	30A/30A	30A/30A	
Battery Input Data							
Battery voltage range	180V~800V						
Battery voltage range for full load	200V~800V	240V~800V	320V~800V	200V~800V	300V~800V	400V~800V	
No. of battery input	1			2			
Nominal charging/discharging power	5000W	6000W	8000W	10000W	15000W	20000W	
Rated charging/ discharging current	25A	25A	25A	50A (25A/25A)	50A (25A/25A)	50A (25A/25A)	
Max. charging/discharging current	25A	25A	25A	50A (25A/25A)	50A (25A/25A)	50A (25A/25A)	



2020-08-25

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)



No.:

GZES2007022915PV

Nominal AC power	5000W	6000W	8000W	10000W	1500	W00	20000W
Max. AC power output to utility grid	5500VA	6600VA	8800VA	11000VA	1650	0VA	22000V/
Max. AC power from utility grid	10000VA	12000VA	16000VA	20000VA	3000	0VA	40000V <i>F</i>
Max. AC current output to utility grid	8A	10A	13A	16A	24	A	32A
Rated AC current output to utility grid	7.2A	8.7A	11.6A	14.5A	21.	7A	29A
Max. AC Current from utility grid	15A	17A	24A	29A	44	A	58A
Nominal output voltage	3/N/PE, 230Vac						
Nominal output freqency	50Hz						
Output power factor	~1(0.8 leading to 0.8 lagging)						
AC Output Data (Back- Nominal output power	up) 5000W	6000W	8000W	10000W	1500	00W	20000W
Max. output power	5500VA	6600VA	8800VA	11000VA	1650	0VA	22000VA
Rated. output current	7.2A	8.7A	11.6A	14.5A	21.	7A	29A
Max. output current	8A	10A	13A	16A	24	A	32A
Nominal output voltage	3/N/PE, 230Vac						
Nominal output freqency			50	Hz			
Output power factor	~1(0.8 leading to 0.8 lagging)						
Operating temperature range	-30°C ~60°C						
Ingress protection	IP65						
Protective class	Class I						
Cooling method	Heat sin	Hea	it sink Hea	at sink	Fan	Fan	Fan
id Guo ior Technical Manage S-CSTC	电子电气实验室	A A A A A A A A A A A A A A A A A A A					2020-08-2

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.