

System Accessories

Datalogger

Wifi Stick/4G Stick



Product Features

Smart and flexible

- Support WiFi configuration and baud rate configuration
- Unobstructed communication distance up to 100m

Simple and efficient

- Plug and play, quick installation
- Upgrade the data collector and inverter by cloud platform and APP

Safe and reliable

- Password and encrypted transmission for data protection
- IP65 protection, wide operating temperature range

Technical Specification

| Items | KC762A | KC761B |
|---------------------------|--|--|
| Type | Wifi Stick | 4G Stick |
| Communication Mode | | |
| RS485 communication | Support 4800/9600/115200bps communication distance ≤100m | |
| WLAN communication | IEEE802.11b/g/n 2.412GHz~2.484GHz | LTE-FDD B1/B3/B5/B7/B8/B20/B28 LTE-TDD B38/B40/B41 GSM 850MHz/900MHz/1800MHz/1900MHz |
| Power Supply | | |
| DC input voltage | 5~15VDC, 1A@15V | |
| Power consumption | ≤5w | |
| General | | |
| Max. number of devices | ≤10 | |
| Display | LED | |
| Operating temperature | -30~70°C/-22~158°F | |
| Relative air humidity | 0%~100% | |
| Elevation | ≤4000m/13123.36ft | |
| Protection class | IP65 | |
| Dimensions (W×H×D) | 48*130.5*31.4mm/1.89*5.14*1.24in | |
| Mounting type | plug & play | |
| Certification | CE, FCC | CE |

*Specification indexes may be subject to changes without further notice.